



LOUD HORN RINGER

MODEL

PTR-6-90VAC

Telecommunication Concepts, Inc.
329 Oriskany Blvd.
Whitesboro, NY 13492

APPLICATION

The model PTR-6-90VAC is designed to produce a pleasant but **“attention getting”** tone. The PTR-6-90VAC wall mount Loud Horn Ringer will require a 12 to 24 VDC external power supply (Model TCI-324) or equivalent. The application of common audible ringing eliminates the need to program numerous phones to ring in one location such as sales or service centers. The PTR-6-90VAC produces a warbled tone following the incoming ring cycle.

INSTALLATION

Mounting Base Assembly: Fully Adjustable 360 horizontal and 160 vertical. Serrated case and single easy-grip locking handle provide rapid positioning and positive locking. Base is removable for mounting.

Connection:

- Green – Tip
- Red – Ring
- Black – -24 VDC
- Yellow – GRD

Models: Tip & Ring Voltage
75 to 120Vrms



PTR-6-90VAC

Figure 1

SPECIFICATIONS

Color	Desert Sand
Sound Pressure Level	121 DB
Output Frequency	576 to 704 Hz
Power Supply	12-24 VDC
Current	25 ma idle 325 ma (Max on)
TIP & RING: Frequency	16 to 66 Hz
Current Drain	3 to 11 ma (RMS)
NET WEIGHT:	5 LBS.